

Radien zum Dornbiegen

Rohrdurchmesser			Mittlererradius							
Ø	4		10	12	17					
Ø	6		10	13	16	25	45	60	80	
Ø	8		12	16	20	25	27	30	80	
Ø	10		15	20	25	45	50			
Ø	12		18	20	25	27	30	38	48	
Ø	13		40	50						
Ø	14		21							
Ø	15		22.5	30	32.5	37	48			
Ø	16		34	40	50					
Ø	17.2	$\frac{3}{8}$ "	35	48.5						
Ø	18		40							
Ø	19		47.5							
Ø	20		35	37	40	50	60			
Ø	21.3	$\frac{1}{2}$ "	50.6	50.7	76	91	141			
Ø	22		40	45	57	60	65	111		
Ø	25		37.5	53.5	62.5	68	80	94		
Ø	26.9	$\frac{3}{4}$ "	50	65	67.5	80	105			
Ø	28		50	76						
Ø	30		65	75	100	180				
Ø	32		60	80						
Ø	33.7	1"	60	65	84	91	125	160		
Ø	35		70	118						
Ø	36		90							
Ø	38		60	91	100					
Ø	40		80	95						
Ø	42.4	$1\frac{1}{4}$ "	80	90 !	104	106	120	126	150	
Ø	45		70	120						
Ø	48.3	$1\frac{1}{2}$ "	80	100	106	120	124	200	250	
Ø	50		118	150						
Ø	60.3	2 "	100	120	150	300				

Standartradien

Da nicht alle Radien für alle Materialien funktionieren,
muss **zwingend** nachgefragt werden.

! = Bei einem 180° Bogen ist der min. RM 90